



Riley Equipment Company
 6911 Gant Road
 Houston, Texas 77066
 sales@recofiltration.com
 (281) 583-5295 Fax: (281) 583-5299

Carbon Block Cartridges

RECO's Carbon Block Cartridges have increased adsorption from higher exposed small carbon particle makeup. These cartridges also have uniformed micro-porous dual action activated / sediment carbon block construction that eliminates channeling. We use UV welded end caps to ensure stable pressure throughout. This product is FDA compliant for EPA P231 State and Local Microbial Purification Standards, NSF P231 standards for Microbial Purifier Water Treatment Systems, and ANSI/NSF standards 42, 53, and 61. It also meets regulatory requirements for the Californian Act Proposition 65 for drinking water. Our Carbon Block Cartridges can be used under gravity or pressure applications.

- Lengths: up to 40"
- Diameters: 2.5", 4.5"
- Multiple Micron ratings available
- End Caps: 222, 226, Flat Gasket, Fin, Spring

Product Specifications	
Micron Ratings:	1, 3, 5, 10
Construction:	Carbon, Polypropylene
End Caps:	Polypropylene
Max Operating Temperature:	155°F for Polypropylene
Diameter:	O.D. – 2.5" - 4.5" I.D. –1.1" center
Nominal Lengths:	9.75" – 40"
Max Differential Pressure:	7 psid

Building a Part Number							
Carbon Block	Media Cover	Micron	Cartridge Diameter	Cartridge Length	Element Grade	End Cap	Gasket / O-Ring
CB	E	1	S	2	S	2	B
CB	E = Polypropylene	1 3 5 10	S = 2.5" M = 4.5"	2 = 9.75 3 = 10 4 = 19.5 5 = 20 6 = 29.25 7 = 30 8 = 39 9 = 40 C = Custom	S = Standard	1 = DOE 2 = 222/Fin 3 = 222/Spring 4 = 222/Flat 5 = 226/Flat 6 = 226/Fin 7 = 226/Spring 8 = SOE/Spring A = Custom	B = Buna V = Viton® T = Teflon® S = Silicone N = Neoprene D = EPDM